



# Aquashower®

## Replacement Filter Instructions

Please follow these instructions carefully.






### When to change your cartridge

The Multipure Shower Filter (Model No. AQSH) should remove unhealthy free chlorine for a period of 6 to 7 months for the average family of four. Chlorine levels vary from city to city. If you live in an area where the source water contains high levels of suspended solids or where scale buildup in pipes is excessive, you may experience an early reduction in water flow. This may be an indication that you need to replace the cartridge (Model No. AQSF) more frequently than the recommended 6 to 7 months. For best results the housing body should be replaced every 3 years or as needed.

### How to change your AQSF cartridge

1. Remove the shower filter from shower arm.
2. Unscrew cap from filter body and remove used filter cartridge. (Fig. 1)
3. Reposition rubber O-rings if they are dislodged. Place small O-ring in the filter housing body. Place large O-ring into groove in housing cap.
4. Insert replacement filter cartridge into Housing Body. (Fig. 2)
5. Screw Housing Cap back onto Housing Body. (Fig. 3)
6. You may want to clean out the sediment screen at this time as well, see below for instructions.
7. Reconnect filter to shower arm. Hand tighten only.
8. Allow water to run through the filter for 30 to 60 seconds before using.

**IMPORTANT:** To assure that no grains of filtering media are introduced into housing, clean o-rings and cartridge, drop the housing body onto the cartridge, and then screw on the housing cap until tight. (Fig. 3)



7251 Cathedral Rock Drive, Las Vegas, NV 89128  
702.360.8880 • 800.622.9206

[www.multipure.com](http://www.multipure.com)



# Aquashower®

## Replacement Filter Instructions

Please follow these instructions carefully.






### When to change your cartridge

The Multipure Shower Filter (Model No. AQSH) should remove unhealthy free chlorine for a period of 6 to 7 months for the average family of four. Chlorine levels vary from city to city. If you live in an area where the source water contains high levels of suspended solids or where scale buildup in pipes is excessive, you may experience an early reduction in water flow. This may be an indication that you need to replace the cartridge (Model No. AQSF) more frequently than the recommended 6 to 7 months. For best results the housing body should be replaced every 3 years or as needed.

### How to change your AQSF cartridge

1. Remove the shower filter from shower arm.
2. Unscrew cap from filter body and remove used filter cartridge. (Fig. 1)
3. Reposition rubber O-rings if they are dislodged. Place small O-ring in the filter housing body. Place large O-ring into groove in housing cap.
4. Insert replacement filter cartridge into Housing Body. (Fig. 2)
5. Screw Housing Cap back onto Housing Body. (Fig. 3)
6. You may want to clean out the sediment screen at this time as well, see below for instructions.
7. Reconnect filter to shower arm. Hand tighten only.
8. Allow water to run through the filter for 30 to 60 seconds before using.

**IMPORTANT:** To assure that no grains of filtering media are introduced into housing, clean o-rings and cartridge, drop the housing body onto the cartridge, and then screw on the housing cap until tight. (Fig. 3)



7251 Cathedral Rock Drive, Las Vegas, NV 89128  
702.360.8880 • 800.622.9206

[www.multipure.com](http://www.multipure.com)